

**Lacquer options: Acrylic** 

# Cover-Tex® 550

## **LIGHT WEIGHT PVC COATED FABRIC**



Cover-Tex 650



Cover-Tex 750



Cover-Tex 900



Cover-Tex 1050

**Cover-Tex 550®** is a light weight versatile PVC coated fabric with Acrylic lacquering suited to general tarpaulin cover applications and small tents and car park shade covers. Produced under strict ISO quality standards utilising the latest European weaving, coating and lacquering technology to ensure a consistent high-quality product.

## **Product Features:**

- UV stabilised
- Acrylic Lacquered
- High Tenacity Polyester base fabric
- Excellent Hot air and HF weldable
- Mould resistant

Flame Retardancy

Quality management

Warranty

Recyclable

• support by 3 year warranty

#### **Technical specifications Standard** Unit **Value** 550 Total weight g/m2 Surface treatment Top Acrylic Base fabric High tenacity PES 1000 Yarn dtex N^0/cm 18x18 Yarn construction DIN EN ISO 2286-3 Thickness 0.45mm mm 2400/2400 Tensile strength EN ISO 1421 N/5cm DIN 53363 220/220 Tear strength Ν Adhesion EN ISO 2411 N/5cm 90 O^c +70 to -30c Temperature resistance

ISO 9001

### **Product disclaimer:**

The technical data are based on average results obtained from third party testing authorities. Due to production procedures, variation up to +5% can occur.

All technical data is supplied to the best of our current knowledge for guidance purposes and is not legally binding.

The manufacturer reserves the right to alter or modify product specifications and colours without notice and assumes no obligation or liability for the suitability and use of its products other than those applications intended by the manufacturer. The manufacturer assumes no liability in the event

The manufacturer assumes no liability in the event of negligent installation/fabrication or application or choice of fabric



## **Sunfx Textiles LLC**

Available on request

3 years

Yes

PO Box 450008 Dubai, United Arab Emirates Telephone +971 4 884 7933 Fax +971 4 884 7934 Email info@polyfab.ae www.sunfxtextiles.com